

ARA



ARA D-SO

Features

- Brushless DC motor with low noise (30dB)
- Strong beltless drum without belt
- Stable working on 10 rpm
- 999 hr integration timer
- Trustworthy safety device
- Easy to use various size

Technical Specifications

	D-SO1	D-SO2	D-SO3
Motion Type	Reciprocal		
Min./Max. Speed	10~350 rpm		
Speed Accuracy	1%		
Speed Control	1 increment		
Motor /Drive	Brushless DC motor / Beltless direct drive		
Noise (dB)	< 30 dB		
Time Control	999 hr 59 min		
Display	Digital LED (FND)		
Max. load	4.0 kg	9.0 kg	15.0 kg
Max. Capacity of Flasks or Tubes	2 x 2,000 mL, 4 x 1,000 mL 9 x 250/500 mL, 16 x 100 mL	4 x 2,000 mL, 9 x 1,000 mL 16 x 500 mL, 25 x 250 mL 36 x 100 mL	5 x 2,000 mL, 15 x 1,000 mL 24 x 500 mL, 40 x 250 mL 60 x 100 mL
Platform Area, mm	350 x 320	450 x 450	760 x 470
Dimensions (WxDxH, mm)	360 x 360 x 110	470 x 490 x 115	745 x 490 x 115
Net Weight (g)	20 kg	28 kg	40 kg
Power Consumption	40 W		
Power Supply	100 ~ 230V, 50/60 Hz		
Cat. No	AD-SO1	AD-SO2	AD-SO3